

## GC-36



The NIBBLE GC-36 module was developed taking into account security and remote maintenance needs. Therefore, the module can operate completely by itself providing remote maintenance functions, automatic output actuation (actuation on incoming call and on input changes) and automatic input alerts (SMS and audio).

## Technical Details

- 2x16 LCD and capacitive keypad;
- 6 bidirectional input/outputs;
- Micro-USB;
- 150 users;
- SMS and voice message alerts for each input;
- Periodic test calls;
- Disarm code;
- Access levels 2 and 3;
- Output actuation with input changes;
- Output actuation with costless phone call;
- Tamper detection;
- Power supply failure detection;
- Internal antenna (optional external not included);
- Backup 9V battery Ni-MH (not included).

## Table

<b>Power supply</b>	+12/32V
<b>Standby current</b>	30mA @ 15VDC
<b>Communication current</b>	100mA @ 15VDC
<b>Dimensions</b>	116.5x104.5x32mm
<b>Weight</b>	165g (220g with battery)

## Examples



## Related Products



GC-22



GC-25



GSM / IP  
COMMUNICATORS

**NIBBLE®**

Rua Júlio Dinis, 265, 1D  
4785-330 Trofa - Portugal  
41° 20' 14.01" -8° 33' 46.10"

(+351) 252 418 349

[www.nibble.pt](http://www.nibble.pt)

[info@nibble.pt](mailto:info@nibble.pt)